

PRODUCT DESCRIPTION

SignOff™ is a citrus-based graffiti removal product designed for the removal of graffiti-tags, such as: spray paints, primers, ink, felt-pen markers, inks, wax-crayons and more. Non-damaging formula makes graffiti removal fast and effective with easy clean-up. **SignOff™** helps restore the natural surface, ideal for: street & road signs, plexiglass, lexon, painted-surfaces, metals, bathroom-divider and more. **SignOff™** is engineered with Sign-Safe Technology™ and helps graffiti removal technician clean tough graffiti-tagged surfaces.

MAIN FEATURES

- **SignOff™** is a graffiti remover with Sign-Safe Technology™, for signage, painted-surfaces, smooth-sensitive surface removal applications
- **SignOff™** removes aerosol / spray-paint, felt-pen ink markers, wax-crayons & more.
- Easy-to-use, fast-acting, easily wipe the toughest graffiti away with **SignOff™**.
- Stop replacing start restoring the natural substrate.
- Ideal for painted-electrical boxes, street & road signs, plexiglass, lexon, cinder-bathroom-dividers and more.
- An approved product of Los Angeles Unified School District, Los Angeles Metro, Cal Trans and more
- **SignOff™** is VOC Compliance, Biodegradable, **UN1993**
- Packaging: 16oz, 32oz, 1gallon, 5gallon

TECHNICAL DATA

pH: 7.0
Flash Point: >200°F / > 93.3°C
Coverage: 300 - 400 sq. ft./gallon.
Shelf Life: 3-5 years (depending on temp and storage)
VOC: 30% or less

RECOMMENDED SUBSTRATES

SignOff™ is a surface-safe graffiti remover recommended for use on smooth and sensitive surfaces. Designed to remove graffiti-tagging without damaging substrate. Ideal for signs, painted surfaces, plastics, plexiglass, metals, and other non-porous surfaces. metals, plexiglass, fiberglass, most forms of plastics, plywood, drywall, or most smooth-sensitive surfaces. Always test small area before using product.

GENERAL APPLICATION

Directions: Use **SignOff™** full strength. Spray or brush **SignOff™** onto graffiti-tagged areas. Allow product penetrate graffiti from: several seconds to several minutes. Agitate surface tension of the graffiti, with a nylon brush or soft abrasive pad. Finally wipe away graffiti residue with a damp cloth. Repeat, if needed. Please note, that some felt-pen marker, ink and spray-paint shadows may require a follow-up application of **Shadowmaster™** products specially designed to remove any additional residue! To avoid any permanent damage, always test on a hidden area of the surface first.

Road and Street Signs

When removing graffiti on street and road signs, brush directly onto tagged areas. Use brush or broom to agitated graffiti. Apply **SignOff™** 1-2 times in a 1-5 mins, saturate surface with **SignOff™**, do not allow surface to dry-out. Use a damp rag to clean any residue.

Smooth- Sensitive Surfaces

Application of water, before applying **SignOff™** may help insure best results. Brush directly onto tagged areas, using the brush to agitate graffiti. Using a damp rag wipe away residue.

Sunbaked or Aged Graffiti

With highly sunbaked or aged-graffiti, apply, at least 3 times, allow a dwell time of 5-15mins (and in some cases longer). Do not allow surface to dry-out, keep area saturated with **SignOff™**

Inks & Markers

When removing inks & felt-pen markers and/or shadowing caused by inks and felt-pen markers. Use brush or broom soaked with **SignOff™** continuously agitate graffiti-tagged area. Longer dwell time may be need, such as 2-5mins.

FOR INDUSTRIAL USE ONLY, UN#1993 FLAMMABLE LIQUID, ETHYL ALCOHOL (CAS#64-17-5). USE ONLY AS DIRECTED. MANUFACTURER NOT RESPONSIBLE FOR DAMAGE OR INJURY. PRODUCT MAY CAUSE DAMAGE TO SURFACE.

More Info: support@envirotekcorporation.com
Website: www.envirotekgraffiti.com
Sales Rep: 818.793.2323

EnvirotekCorporation
Ultimate Surface Cleaners

EnvirotekCorporation Los Angeles CA 800 533 9317

