

Concrete-Masonry Graffiti Remover

PRODUCT DESCRIPTION

Cornerstone™ is a concrete-masonry graffiti remover, that is a highly effective, cost effective, biodegradable and designed to remove: aerosol spray-paints, primers, inks, markers, wax-crayons and more. From porous: brick, stone and most concrete surfaces including cinder-block, split-face block and exposed aggregate. *All raw material can be found on the EPA Safer Choice ingredients list.* **Cornerstone™** helps restore and revitalizes the natural substrate.

MAIN FEATURES

- **Cornerstone™** works fast & effectively to remove graffiti in one application.
- **Cornerstone™** Removes graffiti, is non-damaging, and helps restore the natural surface.
- **Cornerstone™** outperforms the competition, such as: Bare-Brick, Taginator, Elephant Snot and more
- **Cornerstone™** works on a wide array of concrete-masonry surface, such as slip-face, cinder-block, natural stones, and more
- Save time and save money with **Stoneworks™**

TECHNICAL DATA

pH: 12.7-13.33
Flash Point: 212°F
Coverage: 300 - 400 sq. ft./gallon.
Shelf Life: 3-5 years (depending on temp and storage)
VOC: 30% or less

RECOMMENDED SUBSTRATES

Cornerstone™ concrete-masonry surface, graffiti remover, is recommended for use on unpainted-uncoated: concrete-masonry, stone, brick, pavers, cinderblock, split-face, granite, marble, tile and most cementation surfaces. Not for use on: signs, metals, plexiglass, fiberglass, most forms of plastics, plywood, drywall, or most smooth-sensitive surfaces. Always test small area before using product.

GENERAL APPLICATION

Cornerstone™ recommend application with nylon brush, broom. Apply **Cornerstone™** 2-3, flood coat graffiti-tagged surface. Agitation graffiti tagged areas with brush or broom, as you apply **Cornerstone™**. Always, keep the graffiti-tagged soaked with the product, as long as possible before rinsing. Always pressure-wash for bottom-top, lowest point - highest point.

CONCRETE-MASONRY

When removing graffiti on concrete (such as; side-walks, pour-in-place wall, etc), brush **Cornerstone™** directly onto graffiti-tagged area. Use brush or broom to agitated graffiti. Apply **Cornerstone™** 2-3times in a 5-10mins, saturate surface with **Cornerstone™**, do not allow surface to dry-out.

BRICK, CIDER-BLOCK, SPLIT-FACE

Application of water, before applying **Cornerstone™** may help insure maximum results. Brick, cinder-block, and split-face, rapidly absorbs graffiti-cleaners more so, then other surfaces. Flood graffiti-tagged area, with water before applying **Cornerstone™** Then apply **Cornerstone™** to graffiti-tagging.

SUNBAKED OR AGED-GRAFFITI

With highly sunbaked or aged-graffiti, apply, at least 3 times, allow a dwell time of 15-20mins (and in some cases longer). Do not allow surface to dry-out, keep area saturated with **Cornerstone™**

**FOR INDUSTRIAL USE ONLY. UN#1814.
POTASSIUM HYDROXIDE 1310-58-3. AS DIRECTED.
FOR EXTERIOR/OUTDOOR USE
ONLY.MANUFACTURER NOT RESPONSIBLE FOR
DAMAGE OR INJURY. PRODUCT MAY CAUSE DAMAGE
TO SURFACE. NOT FOR USE ON CHILDREN'S PLAY
EQUIPMENT.**

More Info: support@envirotekcorporation.com
Website: www.envirotekgraffiti.com
Local Sales Rep: 818.793.2323

EnvirotekCorporation
Ultimate Surface Cleaners

EnvirotekCorporation Los Angeles CA 800 533 9317

