

PRODUCT DESCRIPTION

GraffitiCrew™ is non-flammable, non-corrosive, non-prop 65, citrus-blended graffiti remover product designed for the removal of graffiti: aerosol spray-paints, primers, ink, felt-pen markers, inks, wax-crayons and more. Non-damaging formula makes graffiti removal fast and effective, with easy clean-up.

GraffitiCrew™ helps restore the natural surface, ideal for: street & road signs, plexiglass, lexon, painted-surfaces, metals, bathroom-divider and more.

GraffitiCrew™ is engineered with and helps graffiti removal technician clean tough graffiti-tagged: paints, primers, inks, felt pen markers, wax-crayons & more.

MAIN FEATURES

- **GraffitiCrew™** is a graffiti remover with for signage, painted-surfaces, multi-surface, concrete-masonry graffiti removal applications
- **GraffitiCrew™** removes aerosol spray-paint, felt-pen ink markers, wax-crayons & more.
- **GraffitiCrew™** easy-to-use, fast-acting, easily wipe the toughest graffiti away with **GraffitiCrew™**
- Stop replacing start restoring the natural substrate.
- Ideal for painted-electrical boxes, street & road signs, plexiglass, lexon, cinder-bathroom-dividers and more.
- An approved product of Los Angeles Unified School District, Los Angeles Metro, Cal Trans and more
- **GraffitiCrew™** is low VOC, Biodegradable,
- Packaging: 32oz, 1gallon, 5gallon, 55gallon containers

TECHNICAL DATA

pH: 6.8-7.0
Flash Point: N/A
Coverage: 350 - 450 sq. ft./gallon.
Shelf Life: 5+ years (depending on temp and storage)
Low VOC

RECOMMENDED SUBSTRATES

GraffitiCrew™ multi-surface graffiti remover recommended for use on smooth, signs, painted and porous surfaces. Designed to remove graffiti-tagging without damaging substrate. Ideal for signs, painted surfaces, plastics, plexiglass, metals, and other non-porous surfaces. metals, plexiglass, fiberglass, most forms of plastics, plywood, drywall, or most smooth-sensitive surfaces. Always test small area before using product.

GENERAL APPLICATION

Directions: Use **GraffitiCrew™** full strength. Spray, brush, or roll **GraffitiCrew™** onto graffiti-tagged areas. Allow product penetrate graffiti from several seconds to several minutes. Agitate surface tension of the graffiti, with a nylon brush or soft abrasive pad. Finally wipe away graffiti residue with a damp cloth. Repeat, if needed. Please note, that some felt-pen marker, ink and spray-paint shadows may require a follow-up application of **Shadowmaster™** products specially designed to remove any additional residue! To avoid any permanent damage, always test on a hidden area of the surface first.

Road and Street Signs

When removing graffiti on street and road signs, brush directly onto tagged areas. Use brush or broom to agitated graffiti. Apply **GraffitiCrew™** 1-2 times in a 1-5 mins, saturate surface with **GraffitiCrew™**, do not allow surface to dry-out. Use a damp rag to clean any residue.

Painted Surfaces

Application of water, before applying **GraffitiCrew™** may help insure best results. Brush directly onto tagged areas, using the brush to agitate graffiti. Using a damp rag wipe away residue.

Sunbaked or Aged Graffiti

With highly sunbaked or aged-graffiti, apply, at least 3 times, allow a dwell time of 5-15mins (and in some cases longer). Do not allow surface to dry-out, keep area saturated with **GraffitiCrew™**

Concrete-Masonry

When removing on concrete-masonry surfaces. Use brush or broom soaked with **GraffitiCrew™** continuously agitate graffiti-tagged area. Longer dwell time may be need, such as 15-20mins. Pressure-wash away residue.

**FOR INDUSTRIAL USE ONLY. AS DIRECTED
MANUFACTURER NOT RESPONSIBLE FOR DAMAGE
OR INJURY. PRODUCT MAY CAUSE DAMAGE TO
SURFACE.**



More Info: support@envirotekcorporation.com
Website: www.envirotekgraffiti.com
Sales Rep: 818.793.2323

EnvirotekCorporation
Ultimate Surface Cleaners